

Home > Products > ProX Lighting > Lasers (High Power) > BERMUDA 1W RGB ILDA TTL Laser Fixture

SKU: X-LRGB1W ILDA

# This product is discontinued

# **BERMUDA 1W RGB ILDA TTL Laser Fixture**

## **Product Images**



#### **Our Products And You**

Submit your story

### ProX X-LRGB1W ILDA BERMUDA 1W RGB ILDA TTL Laser Fixture

### Description

1Watt Class 4 Professional RGB Full Color Animation Laser Effect Light.

UNO Laser's Bermuda line of Laser Display Fixtures is a prime example of where simplicity meets power. Having a professional quality Laser is no longer out of reach for the amature and intermediate Laserist! And it only gets better as we turn up the power.

Bermuda is designed to shoot stunning aerial effects, tunnels, fans, shapes & sheets as well as simple custom graphics, logos, text and much more, with MAXIMUM brightness blanketing your venue in beautiful laser light. And controlling your laser is easy with Pangolin's QuickShow!

Each Uno Laser system will be cleaned and re-calibrated at no extra cost each year for the life of the unit. (Shipping not included)

#### **Features**

Professional RGB Full Color Animation Laser Effect Light with ILDA, Sound, Auto, DMX-512 (12ch.) Control Modes

Laser Power:

Red: 250mw 635nm DPSS diode divergence < 3.5\*0.5mrad beam diameter< 2\*5mm

Green: 150mw 532nm DPSS diode

divergence < 1.5mrad beam diameter< 3mm

Blue: 700mw 445nm DPSS diode

divergence < 2\*0.5mrad beam diameter<2\*5mm

Diode operating temperature:10A?-45A? C warm up time<2 min

70 degree Scan Angle, 25K pps optical scanner

Scanning, projection, or reflection of laser and collateral radiation (light show radiation) into audience or other accessible uncontrolled areas shall not be permitted by any UNO LASER/Xstatic Laser Fixtures.

Control: High capacity & speed microprocessor, ILDA Operation with software such as Pangolin's QuickShow and Beyond System Control packages, High speed optical scanner to generate 3D animated graphics, Sound Sensitivity control, Key operated safety control, Safety mounting point, Adjustable Aperture Beam Blocker, Remote Interlock, Laser classification: EN60825-1 2007 US FDA/CDRH Compliant, One Year Warranty

Uno Laser Variance Information: #2013-V-0607

Check UNO Laser's variance information on: regulations.gov/

**NOTES FROM UNO Laser:** All high-powered laser manufacturers in the USA are required to be compliant with all FDA and CDRH Laser Variances & Regulations.

UNO Laser has gone to extensive lengths to make sure all our Class 3B and Class 4 Laser Display Fixtures are 100% Compliant, Safe, and resilient.

For more detailed information on obtaining your Laser Show Variance, visit our Laser Variance Info page.

#### **Exterior Dimensions & Weight**

6.50"H x 7.00"W x 8.00"L - Weight: 6.00 lbs

#### **Shipping Dimensions & Weight**

Box 1 of 1:8.00"H x 8.50"W x 9.50"L - Shipping Weight: 7.00 lbs

Suggested Shipping Method: Parcel

**UPC** 

019372405351

#### **Our Products and You**

Submit your story

## **Commonly Asked Questions**

+ Where can I buy one?

submit a question

## **Customer Testimonials**

What did you think

### **Related Products**

SKU: XC-ILDA25





Pangolin QuickShow FB3 Control Software with ILDA Interface SKU: X-QUICKSHOWFB3



TWISTER Fog Machine 1220 Watt Water Based w RGBA LED SKU: X-T1220 LED



Professional Stage Portable Fog Machine Vertical Spray DJ Effects DMX RGBA LED Lighting System.
SKU: X-TORNADO-LED