



Home > Products > ProX Cables > > 1000 Ft. High Performance DMX Male 5-Pin Bulk Spool Cable


SKU: XC-DMX5P1000FT

Permalink:

[Search on Google](#)

## 1000 Ft. High Performance DMX Male 5-Pin Bulk Spool Cable

### Product Images



[Download Product Images](#)



[Find A Dealer](#)

### Our Products And You

[Submit your story](#)

### ProX XC-DMX5P1000FT 1000 Ft. High Performance DMX Male 5-Pin Bulk Spool Cable

#### Description

ProX **XC-DMX5P1000FT** 1000 Ft. High Performance **DMX Male 5-Pin Bulk Spool Cable**. ProX Live Performance Gear Cables are made to last you an entire lifetime. Each cable is made with high-quality materials and delivers a clear signal and connection each time. These cables are made by professionals for professionals like you. Each cable is built for High Performance and to withstand heavy everyday use.

**Cable Type:** DMX Spool Cable

**Connector 1:** N/A

**Connector 2:** N/A

**Specification:** Balanced

#### The Build

Our cables are plated with gold and silver connectors for superior signal transfer. 12 AWG – Tin Copper Conductors (TCC) which provide an optimum signal transfer.

#### Quality Control

We test every single cable to make sure each one performs to the best of its ability, which includes high performance and flexibility that can handle heavy everyday use. These cables are specifically designed to provide many years of crystal-clear sound and durability.

## Technical Specifications

Polyethylene insulation

Twisted Quad Data Cable

Polyethylene inner jacket

Duofoil® (100% coverage)

Cotton plus a tinned copper braid shield (85% coverage)

PVC jacket for durability

Nominal Characteristic Impedance: 110 Ohms

Nominal Capacitance Conductor to Conductor @ 1KHz: 12.8 pF/ft

Nominal Cap Cond. To Other Cond. & Shield @ 1KH z: 23 pF/ft

Nominal Velocity of Propagation: 66%

Nominal Delay: 1.6 Nanoseconds per foot

Nominal Conductor DC Resistance @ 20 degrees C: 24 Ohms/1000 ft

Nominal Outer Shield DC Resistance @ 20 degrees C: 3.4 Ohms/ 1000 ft

Nominal Attenuation (dB/100 ft): 0.6 (@ 1 MH z) dB/100 ft

Maximum Recommended Current: 2.1 Amps per conductor @ 25 degrees C

Operating Temperature Range: (-30 degrees C To + 75 degrees C)

---

### Features

- **22 AW TC-Tinned Copper Conductor**
  - **Flexible PVC Jacket**
  - **Limited Lifetime Warranty**
- 

### Shipping Dimensions & Weight

**Box 1 of 1:** 10.20"H x 10.20"W x 21.50"L - Shipping Weight: 48.00 lbs

**Suggested Shipping Method:** Parcel

### UPC

804589618874

### Master Box

QTY 1 pcs

10.20"L x 11.80"D x 10.20"H

Shipping Weight: 28.00 lbs

**Number of Master Boxes: 1**

---

### Our Products and You

Submit your  
story

---

### Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

---

### Customer Testimonials

What did you think

---

### Related Products



#### 6" DMX Male 3-Pin to DMX Female 5-Pin Coupler Patch Cable

SKU: XC-DMX3M5F



#### 6" DMX Male 5-Pin to DMX Female 3-Pin Coupler Patch Cable

SKU: XC-DMX5M3F



#### DMX Male 5-pin Terminator Locking Plug Connector

SKU: XC-DMX5PTR



---

**3 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable**

SKU: XC-DMX03



---

**5 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable**

SKU: XC-DMX05

---