

Our office is closed on Monday April 29th & Tuesday April 30th for Passover



Home > Products > ProX Cables > DMX > 16 Ft. IP66 Outdoor DMX Extension Cable

SKU: XC-IPDMX-EX16

This product is discontinued

16 Ft. IP66 Outdoor DMX Extension Cable

Product Images



[Download Product Images](#)

Our Products And You

Submit your
story

ProX XC-IPDMX-EX16 16 Ft. IP66 Outdoor DMX Extension Cable

Description

ProX XC-IPDMX-EX16 16' DMX signal extension cable w/ IP66 rated Connectors.

ProX cables are built with uncompromised quality with excellent performance at each connection - Instrument cables, Speaker cables, RCA cables, DMX cables, Power cables and more. Our cables are made for professionals, by professionals. Uncompromised signal power, with precise data transmission, is paramount for quality DMX control operations. Our DuoFoil and braided OFC Copper Compact shield blocks noise and protects data transfer.

NOTE: Twisted pair DMX data transmission cables are not suitable for audio use. Conversely, audio cables are not suitable for DMX data use. Their specifications and characteristics differ substantially. Always use the correct cable for reliable connections!

Technical Specifications:

Polyethylene insulation
Twisted Pair Data Cable
Polyethylene inner jacket
Duofoil® (100% coverage)
Cotton plus a tinned copper braid shield (85% coverage)
PVC jacket for durability
Nominal Characteristic Impedance: 110 Ohms
Nominal Capacitance Conductor to Conductor @ 1KHz: 12.8 pF/ft
Nominal Cap Cond. To Other Cond. & Shield @ 1KHz: 23 pF/ft
Nominal Velocity of Propagation: 66%
Nominal Delay: 1.6 Nanoseconds per foot
Nominal Conductor DC Resistance @ 20 degrees C: 24 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 degrees C: 3.4 Ohms/ 1000 ft
Nominal Attenuation (dB/100 ft): 0.6 (@ 1 MHz) dB/100 ft
Maximum Recommended Current: 2.1 Amps per conductor @ 25 degrees C
Operating Temperature Range: (-30 degrees C To + 75 degrees C)

Features

- **Gold/Silver Plated Contacts**
- **ProX IP66 Rated XLR Connectors**
- **Excellent Durability and Superior Data Transfer**

- 20 AWG x 2 Oxygen-Free Copper (OFC) conductors
- Extra Durable & Flexible Long Life Construction
- ProX Limited Lifetime Warranty

Shipping Dimensions & Weight
Shipping Weight: 3.00 lbs

UPC
None

Our Products and You

Submit your
story

Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

Customer Testimonials

What did you think

Related Products



25 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable
SKU: XC-DMX25



50 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Cable
SKU: XC-DMX50