

**Our office is closed on Monday April 29th & Tuesday April 30th for Passover**



Home > Products > ProX Cables > DMX > 3 Ft. Outdoor DMX Adapter Cable XLR3-M to IP66 rated XLR3-F

SKU: XC-IPDMXM01

**This product is discontinued**

## 3 Ft. Outdoor DMX Adapter Cable XLR3-M to IP66 rated XLR3-F

### Product Images



[Download Product Images](#)

### Our Products And You

Submit your  
story

#### ProX XC-IPDMXM01 3 Ft. Outdoor DMX Adapter Cable XLR3-M to IP66 rated XLR3-F

##### Description

**ProX XC-IPDMXM01** 3 Ft. DMX adapter cable XLR3-M to IP66 rated XLR3-F

ProX cables are built with uncompromised quality with excellent performance at each connection - Instrument cables, Speaker cables, RCA cables, DMX cables, Power cables and more. Our cables are made for professionals, by professionals.

We know cables are not just cables, they are what protects your signal from being altered. Uncompromised signal power, with precise data transmission, is paramount for quality DMX control operations. Our DuoFoil and braided OFC Copper Compact shield blocks noise and protects data transfer.

***NOTE: Twisted pair DMX data transmission cables are not suitable for audio use. Conversely, audio cables are not suitable for DMX data use. Their specifications and characteristics differ substantially. Always use the correct cable for reliable connections!***

##### Technical Specifications:

Polyethylene insulation  
Twisted Pair Data Cable  
Polyethylene inner jacket  
Duofoil® (100% coverage)  
Cotton plus a tinned copper braid shield (85% coverage)  
PVC jacket for durability  
Nominal Characteristic Impedance: 110 Ohms  
Nominal Capacitance Conductor to Conductor @ 1KHz: 12.8 pF/ft  
Nominal Cap Cond. To Other Cond. & Shield @ 1KH z: 23 pF/ft  
Nominal Velocity of Propagation: 66%  
Nominal Delay: 1.6 Nanoseconds per foot  
Nominal Conductor DC Resistance @ 20 degrees C: 24 Ohms/1000 ft  
Nominal Outer Shield DC Resistance @ 20 degrees C: 3.4 Ohms/ 1000 ft  
Nominal Attenuation (dB/100 ft): 0.6 (@ 1 MH z) dB/100 ft  
Maximum Recommended Current: 2.1 Amps per conductor @ 25 degrees C  
Operating Temperature Range: (-30 degrees C To + 75 degrees C)

### Features

- Gold/Silver Plated Contacts
- ProX Branded, High-Quality XLR Connectors

- Excellent Durability and Superior Data Transfer
- 20 AWG x 2 Oxygen-Free Copper (OFC) conductors
- Extra Durable & Flexible Long Life Construction
- ProX Limited Lifetime Warranty

---

#### Shipping Dimensions & Weight

Shipping Weight: 1.00 lbs

#### UPC

None

---

#### Our Products and You

Submit your  
story

---

#### Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

---

#### Customer Testimonials

What did you think

---

#### Related Products



##### 3' Ft. High Performance 1/4" TS Male to Dual 1/4" TS Male Unbalanced Audio Cable

SKU: XC-DP03



##### 50 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Cable

SKU: XC-DMX50



##### 25 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable

SKU: XC-DMX25

---