Find A Dealer



Home > Products > ProX Cables > DMX > 5 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable

SKU: XC-DMX05

Permalink: http://www.proxdire

Search on Google

5 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable

Product Images







Download Product Images

Our Products And You

Submit your story

ProX XC-DMX05 5 Ft. DMX Male 3-Pin to DMX Female 3-Pin High Performance Cable

Description

ProX XC-DMX05 5 Ft. DMX Male 3-Pin to DMX Female 3-Pin High-Performance Cable. High-Performance DMX Male 3-Pin to DMX Female 3-Pin Cable High-Performance DMX Male 3-Pin to DMX Female 3-Pin Cable. DMX Cables are used for a vast amount of applications. From Stage Lighting Controllers, Audio Consoles, Mobile DJ Gear, and equipment for Musicians. DMX cables are the bridge to put the control in your hands when it comes to gear.

The Build

Our cables are plated with gold and silver connectors for superior signal transfer. 12 AWG – Tin Copper Conductors (TCC) which provide an optimum signal transfer.

Quality Control:

We test every single cable to make sure each one performs to the best of its ability, which includes high performance and flexibility that can handle heavy everyday use. These cables are specifically designed to provide many years of crystal-clear sound and durability.

Bending, Twisting, are no match for our high-performance tour-grade audio cables. They're designed to provide years of dependable sound reproduction and outlast every other cable on the market! Complete Coil technology demands consistent weave tolerances to create precise accuracy and detailed clarity. This is the most important part of the design and greatly affects performance.

We make Instrument cables, Speaker cables, RCA cables, DMX cables, Power cables, and more. Our cables are made for professionals, by professionals.

Technical Specifications

- Polyethylene insulation
- Twisted Quad Data Cable
- Polyethylene inner jacket
- Duofoil® (100% coverage)
- Cotton plus a tinned copper braid shield (85% coverage)
- PVC jacket for durability
- Nominal Characteristic Impedance: 110 Ohms
- Nominal Capacitance Conductor to Conductor @ 1KHz: 12.8 pF/ft
- Nominal Cap Cond. To Other Cond. & Shield @ 1KH z: 23 pF/ft
- Nominal Velocity of Propagation: 66%
- Nominal Delay: 1.6 Nanoseconds per foot

- Nominal Conductor DC Resistance @ 20 degrees C: 24 Ohms/1000 ft
- Nominal Outer Shield DC Resistance @ 20 degrees C: 3.4 Ohms/ 1000 ft
- Nominal Attenuation (dB/100 ft): 0.6 (@ 1 MH z) dB/100 ft
- Maximum Recommended Current: 2.1 Amps per conductor @ 25 degrees C
- Operating Temperature Range: (-30 degrees C To + 75 degrees C)

Features

- · ProX Branded, All Metal Connectors
- Excellent Durability and Superior Data Transfer
- 22 AW TC-Tinned Copper Conductor
- · Gold- & Silver-Plated contacts
- Tough Metal / Plastic Chassis
- Flexible PVC Jacket
- · Limited Lifetime Warranty

Shipping Dimensions & Weight

Box 1 of 1: 1.00"H x 3.00"W x 7.00"L - Shipping Weight: 0.60 lbs

Suggested Shipping Method: Parcel

UPC

22099559757

Master Box

QTY 10 pcs 5.00"H x 7.00"W x 11.00"L Shipping Weight: 6.00 lbs Number of Master Boxes: 1

Master Box

QTY 50 pcs 8.00"H x 12.00"W x 24.00"L Shipping Weight: 29.00 lbs Number of Master Boxes: 5

Our Products and You

Submit your story

Commonly Asked Questions

+ Where can I buy one?

submit a question

Customer Testimonials

What did you think

Related Products



3 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable SKU: XC-DMX03



 $\underline{\bf 5}$ Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable SKU: XC-DMX05







25 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable SKU: XC-DMX25



Show More