



Home > Products > ProX Lighting >> ELITE 3 ILDA Laser Light Fixture

SKU: X-ELITE3ILDA

Permalink:

[Search on Google](#)

## ELITE 3 ILDA Laser Light Fixture

[Find A Dealer](#)

### Product Images



[Download Product Images](#)

### Our Products And You

[Submit your story](#)

### ProX X-ELITE3ILDA ELITE3ILDA Laser Light Fixture

#### Description

The Unity Elite 3 ILDA is a full color RGB, diode-based laser system, designed for clients who want to produce high impact aerial beam effects, as well as higher output laser graphics, logos and text.

The Elite 3 ILDA is also integrated into a robust IP54 rated housing, making it ideal for life on the road.

#### Applications

The Elite 3 is perfect for small to medium sized venues (up to around 3,000 people in capacity), as well as for DJs, clubs, weddings, theaters, or clients and venues needing a high impact laser system, at a more aggressive price point.

The fixture can also be used both indoors and outdoors, for the projection of laser graphics, logos, text and laser billboard advertisements.

#### Control

Unity Elite ILDA series lasers are incredibly easy to setup and use. And can easily be controlled via ILDA, or via DMX / ArtNET (with Pangolin software).

We recommend using the Pangolin FB3QS or FB4 control hardware, with QuickShow software. Try a FREE demo, and see it in action here: <http://www.pangolin.com/quickshow>.

#### What's in the box?

The Elite 3 ILDA package includes all of the accessories you'll need right out of the box.

Elite 3 ILDA Laser Projector  
Protective travel case  
ILDA cable  
E-stop safety system and E-stop cables  
Interlocks  
Keys

#### Features

Product Name: ELITE 3  
Type: full-colour, semiconductor diode laser system  
Guaranteed optical output: 3100mW

Suitable for: indoor/small outdoor laser shows and laser graphic displays

Control signal: ILDA

Scanning system: 30kpps at 45° with Quickshow test picture

Scanning angle max 45°

Compliant with: EN 60825-1, FDA

Weight: 8kg

Package includes: Heavy duty flight case, power cord, 10M ILDA cable, E-STOP remote with 10M 3-pin XLR cable, set of 4 safety keys, 3-pin interlock bypass plug, user guide.

R | G | B [mW]: 650 | 700 | 1750

Beam size [mm]: 2 x 4

Beam divergence: <1mrad [full angle]

Modulation: 100 | analog

Power requirements: 100-230V/50Hz

Consumption: max. 250VA

Operation temperature: 10-40 °C

Ingress protection rating: IP54

System features: All the adjustments such as power output of each colour, X & Y axes invert, X & Y size and position, etc. Scanning system protection, daisy chain of emergency STOP signal for multiple system "one-hit" operation.

Laser safety features: Keyed interlock, emission delay, magnetic interlock, scan-fail safety, mechanical shutter, adjustable aperture masking plate.

\*Due to Advanced Optical Correction technology used in our laser systems the optical power output of each laser colour within the system may slightly differ from the specification of respective laser module(s) installed. This does not affect the total guaranteed power output.

Dimensions: Length: 238

Width: 246

Height: 163

---

### Suggested Shipping Method: Parcel

#### UPC

850023147073

---

### Our Products and You

Submit your story

---

### Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

---

### Customer Testimonials

What did you think

---