



[Home](#) > [Products](#) > [ProX Truss](#) > [Truss Clamps](#) > [One Ton Capacity Beam Clamp](#)

SKU: XT-LMBC-1

This product is discontinued

One Ton Capacity Beam Clamp

Product Images



[Download Product Images](#)

Our Products And You

Submit your
story

ProX XT-LMBC-1 One Ton Capacity Beam Clamp For Rigging Stage Truss

Description

ProX XT-LMBC-1 beam Clamps are designed to be used as a temporary or permanent fixed position lifting point for overhead rigging without drilling or welding. Beam Clamps are designed also to reduce the I-beam flange stress by distributing loads away from the flange edges during overhead lifting applications.

Using beam clamps safely

- Ensure that the beam clamp is of correct capacity for the load being lifted and that the beam will not be damaged by localized overloading.
- Ensure that the clamp is fitted correctly over the center of gravity of the item being lifted and will not be subjected to side loading.
- Before lifting a load, ensure that the clamp has been tightened and that the lifting appliance is fitted correctly into the eye of the clamp.

In-service inspection and maintenance

- Ensure that beam clamps are kept clean and moving parts are lubricated.
- Regularly inspect beam clamps for wear, damage, distortion, cracks, and any defects likely to cause danger.
- If any of the above defects are found, remove the beam clamp from service and refer to a competent professional.

Features

Rugged all-steel construction
Fits wide range of beam sizes
Black CED finish (Cathodic Electro Deposition)
Tagged for traceability
Built-in suspension bar for easy attachment to load
Fits flange width range of 3-9 inches
Permanent or temporary mounting
Load bar diameter = 1 inch
9 lbs/Each

Our Products and You

Submit your story

Commonly Asked Questions

Ask a question

Customer Testimonials

What did you think